



SBS GRADE

JK ULTIMA:

- Bluish white tinted board with high whiteness coated on both side, double coat on top side and single on bottom side with blade coating.
- Good smoothness on top surface.
- Good bulk and stiffness.
- FDA Reach ROHS certified.
- FSC Mix can be produced.
- Suitable for high speed printing machines with multicolour printing.

Application : Premium packaging of Personal care products, Pharma, Greeting cards, Docket Folders, Hang tags, Bindi, etc.

AVAILABLE IN : 200-400 GSM

PRODUCT SPECIFICATION

PARAMETER	UNIT	VALUES
GSM Range	gsm	200- 400 $\pm$ 3%
BULK	cm ³ /g	1.42-1.50 $\pm$ 5%
Plybond GSM $\geq$ 300	(J/m ²)	$\geq$ 140
Plybond GSM $\leq$ 295	(J/m ²)	$\geq$ 130
Roughness (PPS)	microns (μ)	1.5 (Max)
IGT Dry pick (MV)	m/s	1.2 (Min)
ISO Brightness TS	(%)	90 $\pm$ 1
ISO Brightness BS	(%)	90 $\pm$ 1
C.I.E. Whiteness TS	(%)	125 (Min)
C.I.E. Whiteness BS	(%)	125 (Min)
Gloss at 75o (%)	(%)	45 $\pm$ 5
Cobb 60 - T/S	g/m ²	30 $\pm$ 5
B/S	g/m ²	35 $\pm$ 5
Moisture 200 - 400 gsm	(%)	6.0 - 8.5
Stiffness	MN (MD)	126 - 832
	MN (CD)	63 - 451